



AKKU K6-4.5




General Features

- High corrosion resistant performance: Pb-Ca multi-alloy grid
- High energy density and power density
- Optimized capability of instant high-current discharging
- Excellent charge acceptance ability
- Excellent deep cycle discharge capability
- Strong high and low temperature performance
- Precision sealing technology



Dimension: 71(L)×47(W)×97(H)×101(TH) Unit: mm



Applications

- UPS/EPS
- Power systems
- Telecommunications system
- Emergency lighting, Auto control system
- Solar/wind generating storage cyclic
- Other general purpose

Specification

Nominal Voltage	6V
Nominal Capacity	4.5Ah
Design life	5 years
Terminal	F187
Approx. Weight	Approx0.75kg (1.65lbs)
Container Material	ABS
Rated Capacity	4.50Ah ➤ 20Hour Rate (0.225A to 5.25V)
	3.51Ah ➤ 3Hour Rate (1.17A to 5.25V)
	2.97Ah ➤ 1Hour Rate (2.97A to 4.80V)
Internal resistance	Full charged at 25°C: 25.0 mΩ
Max. Discharge Current	67.5A(5S)
Operating Temperature	Discharge: -20 ~50°C(-4~ 122°F)
	Charge: -20 ~50°C(-4~ 122°F)
	Storage: -20 ~50°C(-4~ 122°F)
Charge current:	Max.1.13A ; Recom.0.45A
Charge Method (25 °C)	Float Charge:6.75-6.90V,recom.6.90V(-9mV/ °C)
	Equalize charge:6.90-7.05V,recom.7.05V(-12mV/ °C)
	Cycle charge:7.20-7.50V,recom.7.35V(-15mV/ °C)
Self discharge	3% of capacity declined per month at 25°C

Constant Current Discharge Characteristics Unit: A (25°C, 77°F)

FV/Time	5min	10min	15min	30min	1h	2h	3h	4h	5h	8h	10h	20h
1.60V	17.8	11.7	8.69	5.69	2.97	1.70	1.24	0.995	0.846	0.558	0.446	0.239
1.65V	17.7	11.2	7.97	5.40	2.79	1.63	1.21	0.963	0.828	0.549	0.441	0.234
1.70V	14.5	10.5	7.43	5.24	2.70	1.60	1.18	0.914	0.819	0.540	0.432	0.230
1.75V	13.5	10.0	6.93	5.12	2.61	1.56	1.17	0.900	0.783	0.527	0.423	0.225
1.80V	12.4	9.41	6.44	4.95	2.52	1.52	1.10	0.882	0.752	0.513	0.414	0.216


Constant Power Discharge Characteristics Unit: W/cell (25°C, 77°F)

FV/Time	5min	10min	15min	30min	1h	2h	3h	4h	5h	8h	10h	20h
1.60V	33.5	21.0	15.9	9.62	5.45	3.19	2.35	1.88	1.60	1.05	0.863	0.473
1.65V	30.8	19.9	14.9	9.55	5.12	3.07	2.28	1.82	1.57	1.04	0.847	0.460
1.70V	28.2	19.3	14.3	9.52	4.97	3.01	2.24	1.73	1.52	1.03	0.840	0.456
1.75V	25.6	18.7	13.7	9.42	4.82	2.94	2.21	1.71	1.49	0.985	0.821	0.446
1.80V	23.0	18.1	13.1	9.35	4.76	2.92	2.15	1.70	1.46	0.952	0.804	0.443


Disclaimer: Manufacturers have the right to self-modify the parameters of the product updates, please keep in touch with manufacturers to obtain the latest information.

AKKU K6-4.5


Discharge characteristic




Charging characteristic




The effect of temperature on capacity



The effect of discharge depth on cycle life



Curves of self-discharge



The effect of temperature on float life

