

KCD12-105

Description

Krafton Deep Cycle is suitable for deep cycle applications due to an extreme cyclic stability. The robust character of these batteries makes them resistant to deep discharges up to 80%! Outstanding performance and durability makes Krafton Deep Cycle the ideal choice for industrial applications such as aerial platforms, scissor lifts, forklifts, sweepers, golf carts and traffic support as well as marine and leisure vehicles with medium to high power consumers. Available in a range of 6V/8V/12V batteries up to 360Ah in series Deep Cycle, AGM and Tubular.

Performance	
Nominal Voltage	12
Capacity	105Ah (100hr, 1.75V/cell)
Capacity	85Ah (5hr, 1.7V/cell)
RC 25A	180

Technical Charact	eristics	
Technology	VRLA	
Seperator	AGM	

Charging instructions	
Cycle use charge recommendation, Voltage	14.4
Cycle use charge recommendation, Max Amps	20
Float charge recommendation, Voltage	13.62
Float charge recommendation, Max Amps	1
Cycles at 50% DoD	600
Boost and float charge MUST be	e compensated according to temperature. In Flooded, this is

Boost and float charge MUST be compensated according to temperature. In Flooded, this is desirable, but not mandatory. The voltage is adjusted by the formula: $(-5mV \times (T \text{ battery } - 25 ^\circ))$



Features

- Extreme power supply
- Deep discharges up to 80%
- Extreme cycle stability
- Recommended for industrial applications and marine and leisure vehicles.
- Available as deep cycle, AGM or tubular batteries

Layout	Terminal	Hold-down
_ +	⊕ 19,5	100 max 100 max

Battery Classifications as per EN 50342-6						
Water Consumption	Charge Retention	Vibration Resistance	Endurance Level	Micro-Cycle Performance		
W4	C2	V3	E4	M2		